


A Composable Specification Language for Reinforcement Learning Tasks

Kishor Jothimurugan, Rajeev Alur, Osbert Bastani




Control System



S = Set of System States
 A = Set of Control Inputs

- Continuous states and actions
- System can be probabilistic
- Discrete Time
- Finite time horizon - T

Reinforcement Learning




S = Set of System States
 A = Set of Control Inputs

- Use neural networks to map states to actions
- **Design reward function R mapping runs to rewards**
- Learn NN parameters optimizing:

$$\pi^* \in \operatorname{argmax}_{\pi} \mathbb{E}_{\rho \sim \mathcal{D}_{\pi}} [R(\rho)]$$

Reward Functions

- Too low-level as compared to logical specification
- No obvious way to compose rewards




R_1 : Reward function for “Reach q ”

R_2 : Reward function for “Reach p ”

Reward function for “Reach q and then Reach p ” ?

Need to generate reward function from a given logical specification

Need For Memory



- Specification: Reach q , then Reach p , then Reach r
- Controller maps states to actions
- Action at p depends on the history of the run

Solution: Add additional state component to indicate whether q has already been visited

Need to generate reward function from a given logical specification

Need to automatically infer the additional state components from the specification


Our Framework

- **System MDP** $= (S, A, P, T, s_0)$ where $P(s, a, s') = \Pr(s'|s, a)$ given as a black-box forward simulator
- **Specification** φ given in our task specification language

Synthesizes a control policy π^* such that,

$$\pi^* \in \operatorname{argmax}_{\pi} \Pr[\rho \models \varphi]$$

Our Framework



Task Specification Language

$$\phi := \text{achieve } b \mid \phi_1 \text{ ensuring } b \mid \phi_1; \phi_2 \mid \phi_1 \text{ or } \phi_2$$

➤ Example base predicates:

- $Near_q$ is satisfied if and only if the distance to q is less than 1
- $Away_o$ is satisfied if and only if there is a positive distance to o

➤ Specification for navigation example:

$$(\text{achieve } Near_q; \text{achieve } Near_p) \text{ ensuring } Away_o$$

Quantitative Semantics


- Assume each base predicate $b \in P$ is associated with a quantitative semantics, $\llbracket b \rrbracket: S \rightarrow \mathbb{R}$ such that,

$s \models b$ if and only if $\llbracket b \rrbracket(s) > 0$

- $\llbracket Near_q \rrbracket(s) = 1 - dist(s, q)$
 - $\llbracket Away_o \rrbracket(s) = dist(s, O)$
- Extend to positive Boolean combinations by,
 - $\llbracket b_1 \vee b_2 \rrbracket = \max(\llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket)$
 - $\llbracket b_1 \wedge b_2 \rrbracket = \min(\llbracket b_1 \rrbracket, \llbracket b_2 \rrbracket)$


Task Monitor

- Finite State Machine
- Registers that store quantitative information
- Compilation similar to NFA construction from regular expressions



Task Monitor for $\phi = \text{achieve } b$


Task Monitor



Task monitor for $(\text{achieve } \text{Near}_q ; \text{achieve } \text{Near}_p)$ ensuring Away_o

$u: x_3 \leftarrow \min(x_3, \text{dist}(s, O))$

Extended Policy



Assigning Rewards


Given a sequence of extended system states, $\rho = (q_0, s_0, v_0) \rightarrow \dots \rightarrow (q_T, s_T, v_T)$ what should be its reward?

- Case 1: (q_T is a final state) Reward is given by monitor
- Case 2: (q_T not a final state) Not all tasks have been completed
 - Suggestion 1: $R(\rho) = -\infty$
 - Suggestion 2: Find a reward function R' that preserves ordering of runs w.r.t. R ,

$$R(\rho) > R(\rho') \text{ implies } R'(\rho) > R'(\rho')$$

Reward Shaping

Given $\rho = (q_0, s_0, v_0) \rightarrow \dots \rightarrow (q_T, s_T, v_T)$ with q_T non-final,




- d_q : Length of the longest path from q_0 to q without using self loops
- C_l : Lower bound for possible reward in any final state
- C_u : Upper bound on the third term for all q

Experiments


- Implemented our approach in a tool called **SPECTRL** (SPECifying Tasks for RL)
- Case study in the 2D navigation setting:
 - $S = \mathbb{R}^2$ and $A = \mathbb{R}^2$
 - Transitions given by $s_{t+1} = s_t + a_t + \varepsilon$ where ε is a small gaussian noise

2D Navigation Tasks



Learning curves for different tasks

2D Navigation Tasks





Sample Complexity Curve

Y-axis denotes number of sample trajectories needed to learn

X-axis denotes number of nested goals

Cartpole



Learning Curve for Cartpole

Spec: Go to the right and return to start position without letting the pole fall

THANK YOU!